

*In the Claims*

The following is a marked-up version of the claims with the language that is underlined ("\_\_\_") being added and the language that contains strikethrough ("—") being deleted:

1. (Currently amended) A method for facilitating display of a graphic on an electrical device, comprising ~~the steps of~~:

receiving from a user a selection ~~an identification~~ of graphical data representing a the graphic to be transmitted to the electrical device; and

facilitating transmission of the graphical data representing the graphic to the electrical device such that the electrical device can display the graphic in a device control panel.

2. (Currently amended) The method of claim 1, wherein ~~the step of~~ receiving a selection ~~an identification~~ comprises receiving an identification of a location of the graphical data.

3. (Original) The method of claim 2, wherein the graphical data is located at a remote location that is accessible via a network.

4. (Currently amended) The method of claim 1, wherein ~~the step of~~ facilitating transmission of the graphical data comprises transmitting the graphical data along with a job to be performed by the electrical device.

5. (Original) The method of claim 1, wherein the graphical data comprises two or more frames in GIF89a format that can be displayed in sequence to create an animation.

6. (Currently amended) The method of claim 1, further comprising ~~the~~ ~~step of~~ receiving an indication of when ~~how~~ the graphic is to be displayed by the electrical device.

7. (Currently amended) The method of claim 6, wherein ~~the step of~~ receiving an indication of when ~~how~~ the graphic is to be displayed comprises receiving an indication of an electrical device state during which the graphic is to be displayed.

8. (Currently amended) The method of claim 7, wherein the electrical device state comprises at least one of an initialization state, a ready state, an operating state, and a power save state.

9. (Currently amended) A system for facilitating display of a graphic on an electrical device, comprising:

means for receiving from a user a selection ~~an identification~~ of graphical data representing a the graphic to be transmitted to the electrical device; and

means for facilitating transmission of the graphical data representing the graphic to the electrical device such that the electrical device can display the graphic in a device control panel.

10. (Original) The system of claim 9, wherein the graphical data is located at a remote location that is accessible via a network.

11. (Original) The system of claim 9, wherein the means for facilitating transmission of the graphical data comprises means for facilitating transmission of the graphical data along with a job to performed by the electrical device.

12. (Original) The system of claim 9, wherein the graphical data comprises two or more frames in GIF89a format that can be displayed in sequence to create an animation.

13. (Original) The system of claim 9, further comprising means for receiving an indication of an electrical device state during which the graphic is to be displayed.

14. (Currently amended) A method for facilitating display of a graphic on an electrical device, comprising the steps of

receiving graphical data that has been selected by a user from a computing device;

receiving an indication as to how the a graphic represented by the selected graphical data is to be displayed; and

displaying the graphic in a device control panel according to the received indication.

15. (Currently amended) The method of claim 14, wherein ~~the step of~~ receiving graphical data comprises receiving the graphical data along with a job to be performed by the electrical device.

16. (Currently amended) The method of claim 14, wherein ~~the step of~~ receiving an indication as to how the graphic is to be displayed comprises receiving an indication of an electrical device state during which the graphic is to be displayed.

17. (Currently amended) The method of claim 14, wherein the electrical device state comprises at least one of an initiation state, a ready state, an operating state, and a power save state.

18. (Original) The method of claim 14, wherein the graphical data comprises two or more frames that can be displayed in sequence to provide an animation.

19. (Currently amended) A system for facilitating display of a graphic on an electrical device, comprising:

means for receiving graphical data that has been selected by the user from a computing device;

means for receiving an indication as to how ~~a the~~ graphic represented by the selected data is to be displayed; and

means for displaying the graphic in a device control panel according to the received indication.

20. (Original) The system of claim 19, wherein the means for receiving graphical data comprises means for receiving the graphical data along with a job to be performed by the electrical device.

21. (Original) The system of claim 19, wherein the means for receiving an indication as to how the graphic is to be displayed comprises means for receiving an indication of an electrical device state during which the graphic is to be displayed.

22. (New) The method of claim 1, wherein facilitating transmission comprises facilitating transmission of the graphical data to a printing device.

23. (New) The method of claim 22, wherein facilitating transmission comprises facilitating transmission of the graphical data to a printer.

24. (New) The method of claim 4, wherein transmitting the graphical data along with a job comprises transmitting the graphical data along with a print job for the electrical device.

25. (New) The system of claim 9, wherein the means for facilitating transmission comprise means for facilitating transmission of the graphical data to a printing device.

26. (New) The system of claim 25, wherein the means for facilitating transmission comprise means for facilitating transmission of the graphical data to a printer.

27. (New) The system of claim 11, wherein the means for facilitating transmission of the graphical data along with a job comprise means for facilitating transmission of the graphical data along with a print job for the electrical device.

28. (New) The method of claim 14, wherein displaying the graphic in a device control panel comprises displaying the graphic in a printing device control panel.

29. (New) The method of claim 28, wherein displaying the graphic in a printing device control panel comprises displaying the graphic in a printer control panel.

30. (New) The method of claim 15, wherein receiving the graphical data along with a job comprises receiving the graphical data along with a print job.

31. (New) The system of claim 19, wherein the means for displaying the graphic in a device control panel comprise means for displaying the graphic in a printing device control panel.

32. (New) The system of claim 31, wherein the means for displaying the graphic in a printing device control panel comprise means for displaying the graphic in a printer control panel.

b1  
b7C

33. (New) The system of claim 20, wherein the means for receiving the graphical data along with a job comprise means for receiving the graphical data along with a print job.

---